

Fortress™ 300

with  **Microban® Product Protection**



Application

A high-quality construction for hot water up to 200°F (93°C) cleanup service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries, and creameries. Its super abrasion- and oil-resistant cover provides maximum protection against the adverse of oil and animal fats. The cover of Goodyear's Fortress™ 300 hose incorporates Microban's®* anti-microbial built-in product protection.

Construction

- Tube:** Black Nitrile synthetic rubber
- Cover:** Yellow Carbyn® synthetic rubber, RMA Class A (high oil resistance) with Microban® product protection
- Reinforcement:** Spiral synthetic yarn

Temperature

-20°F to 200°F (-29°C to 93°C)

Packaging

- 1/2"-3/4" - 500' reels, maximum 3 pieces, 50' increments
- 1" - 450' reels maximum 3 pieces, 50' increments

Part #	NOM. ID		NOM. OD		MAX. WP		WEIGHT	
	in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
08-FORTRESS-300	1/2	12.70	0.75	19.05	300	2.07	0.29	0.43
10-FORTRESS-300	5/8	15.88	0.86	21.84	300	2.07	0.36	0.54
12-FORTRESS-300	3/4	19.05	1.20	30.48	300	2.07	0.41	0.61
16-FORTRESS-300	1	25.40	1.50	38.10	300	2.07	0.60	0.89

*Microban® antimicrobial product protection inhibits the growth of bacteria, mold, and fungi that can cause odor, stains, or degradation of the hose cover.

Microban® is intended to protect the hose cover only. It is not a substitute for good sanitary practices.

Couplings - Contact D.F. Burnham for proper fitting recommendation.

Industrial Hose



Fortress™ 3000

with  **Product Protection**



Application

Goodyear's Fortress™ 3000 is for use on pressure washer machines with working pressures up to 3000 psi. Applications include washdown in food processing plants, dairies, packing houses, bottling plants, breweries, canneries, and creameries. Its super abrasion- and oil-resistant cover provides maximum protection against the adverse affects of oil and animal fats. The cover of Goodyear's Fortress™ Washdown hose incorporates Microban's®* antimicrobial built-in product protection.

Construction

Tube: Black Nitrile synthetic rubber

Cover: Yellow Carbyn® synthetic rubber, RMA Class A (high oil resistance) with Microbn® product protection

Reinforcement: Braided (1) steel wire

Temperature

-20°F to 200°F (-29°C to 93°C)

Packaging

500' reels, maximum 3 pieces, 50' increments, coupled lengths available

Part #	NOM. ID		NOM. OD		MAX. WP		WEIGHT	
	in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
04-FORTRESS-3000	1/4	6.35	0.53	13.46	3000	20.69	0.15	0.22
06-FORTRESS-3000	3/8	9.53	0.69	17.53	3000	20.69	0.24	0.36
08-FORTRESS-3000	1/2	12.70	0.82	20.83	3000	20.69	0.32	0.48

*Microban antimicrobial product protection inhibits the growth of bacteria, mold, and fungi that can cause odor, stains, or degradation of the hose cover.

Microban is intended to protect the hose cover only. It is not a substitute for good sanitary practices.

Couplings - Contact D.F. Burnham for proper fitting recommendation.

Industrial Hose



Spectra™ 1000

Application

For use on pressure washer machines with working pressures up to 1000 psi. Its abrasion- and oil-resistant cover provides protection against the affects of oil and animal fats.



Construction

Tube: Black Nitrile synthetic rubber

Cover: Yellow Chemivic® synthetic rubber, RMA Class A (high oil resistance)

Reinforcement: Braided (1) steel wire



Temperature

-20°F to 200°F (-29°C to 93°C)

Part #	NOM. ID		NOM. OD		MAX. WP		WEIGHT	
	in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
06-SPECTRA-1000	3/8	9.53	0.69	17.53	1000	6.9	0.21	0.31
08-SPECTRA-1000	1/2	12.70	0.81	20.57	1000	6.9	0.29	0.43
12-SPECTRA-1000	3/4	19.05	1.10	27.94	1000	6.9	0.44	0.65

Note: Not recommended for steam service.

Sani-Wash™ 300

Application

All economical hose for hot water washdown up to 205°F cleanup in food processing plants, dairies, packing houses, bottling plants, breweries, canneries, and creameries.

Construction

Tube: Versigard® synthetic rubber

Cover: White Versigard® synthetic rubber

Reinforcement: Textile reinforced



Temperature

-40°F to 200°F (-40°C to 93°C)

Packaging

1/2"-3/4" - 500' reels, maximum 3 pieces, 50' increments

1" - 450' reels maximum 3 pieces, 50' increments

Part #	NOM. ID		NOM. OD		MAX. WP		WEIGHT	
	in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
08-SANI-WASH	1/2	12.70	0.84	21.34	300	2.07	0.26	0.39
10-SANI-WASH	5/8	15.88	1.00	25.40	300	2.07	0.31	0.46
12-SANI-WASH	3/4	19.05	1.17	29.72	300	2.07	0.42	0.63
16-SANI-WASH	1	25.40	1.48	37.59	300	2.07	0.62	0.92

Couplings - Contact D.F. Burnham for proper fitting recommendation.



Phone 1-800-989-1770

Fax 1-800-989-1774

www.dfburnham.com