

NR Spray



Application

NR Spray is a premium-quality, all-purpose hose for handling a variety of applications such as paint spray or agricultural spray. Will handle spraying paints, automotive finish paints, lacquers, thinners, turpentine, air, oil, and a large variety of solvents and chemicals.

Construction

Tube: Nylon, silicone-free

Cover: Black synthetic rubber, RMA Class B (medium/high oil resistance)

Reinforcement: Braided synthetic yarn (1/4" and 3/8"-1 braid) (1/2", 3/4" and 1"-2 braid)

Temperature

-0°F to 190°F (-18°C to 88177°C)

Packaging

500' reel, maximum 3 pieces, 50' minimum

| Part # | NOM. ID | | NOM. OD | | MAX. WP | | WEIGHT | |
|-------------|---------|-------|---------|-------|---------|------|---------|--------|
| | in. | mm. | in. | mm. | psi. | Mpa. | lb./ft. | kg./m. |
| 04-NR-SPRAY | 1/4 | 6.35 | 0.50 | 12.70 | 750 | 5.17 | 0.08 | 0.12 |
| 06-NR-SPRAY | 3/8 | 9.53 | 0.70 | 17.78 | 750 | 5.17 | 0.15 | 0.22 |
| 08-NR-SPRAY | 1/2 | 12.70 | 0.88 | 22.35 | 750 | 5.17 | 0.22 | 0.33 |
| 12-NR-SPRAY | 3/4 | 19.05 | 1.19 | 30.23 | 750 | 5.17 | 0.36 | 0.54 |
| 16-NR-SPRAY | 1 | 25.40 | 1.51 | 38.35 | 750 | 5.17 | 0.53 | 0.79 |

Couplings - Contact D.F. Burnham for proper fitting recommendation.

Industrial Hose

