

Double Bolt Clamps


A rugged, plated malleable iron two-bolt clamp with machine bolts and hex nuts. Inner surface has dual gripping ridges. Bolt lugs are reinforced to prevent bending out of alignment. Torque values for clamps are based on "dry bolts". The use of lubricant on bolts will adversely effect clamp performance.

*Recommended torque rated in FT. LBS.



SAFETY ALERT

Consult DF Burnham when using double bolt clamps on helical wire hose.



Double bolt clamp without saddles

Part #	Pkg Qty	Torque *	Hose O.D. Range	
			From:	To:
48	100	15	1-8/64"	1-12/64"
R88DB-12	50	21	1-12/64"	1-24/64"
R88DB-16	25	21	1-28/64"	1-34/64"
L14	25	40	1-40/64"	1-52/64"
R88DB-20	25	27	1-48/64"	2-3/64"
R88DB-24	25	27	2-7/64"	2-19/64"
R88DB-32	25	40	2-20/64"	2-40/64"
R88DB-40	25	40	2-32/64"	2-48/64"
R88DB-45	20	60	2-48/64"	3-4/64"
L328	20	60	3-4/64"	3-24/64"
L350	20	60	3-16/64"	3-32/64"

Double bolt clamp with two saddles

Part #	Pkg Qty	Torque *	Hose O.D. Range	
			From:	To:
400	25	40	3-32/64"	3-52/64"
431	20	40	3-50/64"	4-4/64"
463	20	40	4-2/64"	4-18/64"
525	10	60	4-16/64"	4-60/64"
550	10	60	4-32/64"	5-16/64"
600	10	60	5-8/64"	5-44/64"
639	10	60	5-44/64"	5-60/64"
675	10	60	5-60/64"	6-32/64"
769	10	60	6-32/64"	7-36/64"
818	5	125	7-44/64"	8-12/64"
875	5	125	8-16/64"	8-56/64"
988	5	125	8-60/64"	9-56/64"
1125	5	125	9-60/64"	11-24/64"
1275	3	125	11-12/64"	13"
1360	2	200	12-12/64"	14"
1450	2	200	13-12/64"	15"
1700	2	260	15-4/64"	17-32/64"

NOTE: Measure hose O.D. accurately before ordering clamps.

Optional Pkg./Box Quantity Shown

Clamps

Single Bolt Clamps

Torque values for clamps are based on "dry bolts". The use of lubricant on bolts will adversely effect clamp performance



plated malleable iron.
•Recommended torque rated in FT. LBS.

NOTE: Measure hose O.D. accurately before ordering clamps.

Part #	Torque *	Hose O.D. Range	
		From:	To:
2	6	5/64"	1"
3	6	62/64"	1-8/64"
4	6	1-4/64"	1-12/64"
5	6	1-10/64"	1-16/64"
6	6	1-16/64"	1-24/64"
7	6	1-22/64"	1-28/64"
8	6	1-28/64"	1-36/64"
9	6	1-34/64"	1-44/64"
10	6	1-42/64"	1-48/64"
11	6	1-48/64"	1-56/64"
12	6	1-56/64"	2-2/64"
13	12	2"	2-8/64"
14	12	2-8/64"	2-18/64"
15	12	2-16/64"	2-26/64"

Part #	Torque *	Hose O.D. Range	
		From:	To:
16	12	2-24/64"	2-32/64"
17	12	2-32/64"	2-40/64"
18	12	2-40/64"	2-56/64"
19	12	2-56/64"	3-4/64"
20	12	3-4/64"	3-16/64"
21	12	3-16/64"	3-28/64"
22	21	3-28/64"	3-40/64"
23	21	3-40/64"	3-52/64"
24	21	3-52/64"	4-8/64"
25	21	4-8/64"	4-20/64"
26	21	4-16/64"	4-32/64"
27	21	4-28/64"	4-40/64"
X27	21	4-40/64"	4-56/64"
28	21	4-56/64"	5-16/64"

