

**Soft Seat Safety Pop-Off Valves**

ASME Code Safety Valve, National Board Certified for compressed air service applications. Designed for Original Equipment Manufacturers, utilizing ASME Code un-fired pressure vessels in their finished product. Constructed of precision machined brass bar stock, with a silicone disc seating on brass. Maximum operating temperature is **400°F (204°C)**.


1/4" male NPT		
Part #	SCFM	Preset Pressure PSI
<b>KSV10-100</b>	33	<b>100</b>
<b>KSV10-125</b>	40	<b>125</b>
<b>KSV10-150</b>	47	<b>150</b>
<b>KSV10-175</b>	54	<b>175</b>



**Reelcraft® 5000 Series Spring Driven Hose Reels**

With Hose					
Part #	Hose I.D.	Hose Length	Service	PSI	Weight
<b>5450LP</b>	1/4"	50'	Air / Water	<b>300</b>	26
<b>5635LP</b>	3/8"	35'	Air / Water	<b>300</b>	25
<b>5650LP</b>	3/8"	50'	Air / Water	<b>300</b>	37

Without Hose				
Part #	Hose Capacity	Service	PSI	Weight
<b>5600LP</b>	50' of 1/4" or 35' of 3/8"	Air / Water	<b>500</b>	21
<b>5605LP</b>	50' of 3/8"	Air / Water	<b>500</b>	31




- Maximum temperature is **150°F**
- Reel inlet 3/8" NPTF
- All steel construction
- Full full shaft and swivel
- Furnished standard with PVC hose
- Compressed air hose should not be converted to oxygen service. Compressed air hoses are often contaminated with an oil coating, which can react explosively when oxygen is introduced.

**Reelcraft® 7000 Series Spring Driven Hose Reels**

With Hose					
Part #	Hose I.D.	Hose Length	Service	PSI	Weight
<b>7670LP</b>	3/8"	70'	Air / Water	<b>300</b>	50
<b>7850LP</b>	1/2"	50'	Air / Water	<b>300</b>	51

Without Hose				
Part #	Hose Capacity	Service	PSI	Weight
<b>7800LP</b>	70' of 3/8", 50' of 1/2"	Air / Water	<b>500</b>	43
<b>7800MP</b>	50' of 3/8" or 50' of 1/2"	Oil	<b>3000</b>	44
<b>7600HP~</b>	50' of 1/4" or 50' of 3/8"	Grease	<b>5000</b>	46



- All steel construction
- "LP" Low Pressure reels:  
Maximum temperature **150°F**  
Reel inlet 1/2" NPTF  
PVC hose is standard
- "MP" Medium Pressure reels:  
Maximum temperature **210°F**  
Reel inlet 1/2" NPTF  
SAE 100 R1T 1-wire braid hose standard
- "HP" Low Pressure reels:  
Maximum temperature **210°F**  
Reel inlet 1/4" NPTF  
SAE 100 R2T 2-wire braid hose standard

**Hose  
Accessories**

**Reelcraft® 80000 Series Spring Driven Hose Reels**

With Hose					
Part #	Hose I.D.	Hose Length	Service	PSI	Weight
82075LP~	1/2"	75'	Air / Water	300	90
82100LP	1/2"	100'	Air / Water	300	99
83050LP	3/4"	50'	Air / Water	250	89

Without Hose				
Part #	Hose Capacity	Service	PSI	Weight
83000LP~	50' of 3/4" or 100' of 1/2"	Air / Water	500	74




- Maximum temperature is **150°F** *with hose*
- Maximum temperature is **210°F** *without hose*
- Furnished standard with PVC hose
- Reel inlet 3/4" NPTF
- Five-in-one heat treated aluminum casting incorporates main shaft, ratchet, spring arbor and inlet/outlet plumbing in one piece casting. High pressure cast steel.
- Most compact 3/4" x 50' hose reel of its capacity available.

*See next page for bumper stops. Consult factory for uses other than stated services.*

**Adjustable Hose Bumper Stops**

Part #	Hose Diameter		Hose I.D.	Dimensions		Reel Series
	From:	To:		B,C,E	D	
1-HR1004A	.438"	.625"	1/4"	2-1/2"	1-1/4"	5000
1-HR1004	.625"	.749"	3/8"	2-1/2"	1-1/4"	5000
1-HR1004-3	.625"	.749"	3/8"	3"	1-1/4"	7000
2-HR1004-3	.750"	1.050"	1/2" or 3/8" 2-wire	3"	1-1/4"	7000
3-HR1004-3	1.060"	1.300"	3/4"	3"	1-1/4"	7000
2-HR1005	.750"	1.050"	1/2"	3-1/2"	2-7/8"	9000
3-HR1005	1.060"	1.380"	3/4"	3-1/2"	2-7/8"	9000
4-HR1005	1.390"	1.550"	1"	3-1/2"	2-7/8"	9000



*Adjustable Hose Bumper Stops are not included on hose reels ordered without hose. Order separately.*

**Reelcraft® 30,000 Manual Driven Hose Reels**



Without Hose					
Part #	Hose I.D.	Spool Width	Hose Capacity	PSI	Weight
C33112L	3/4"	12"	100'	1000	46
C32112M	1/2"	12"	200'	3000	46

- Unitized construction: Reel frame, spool and drum are fabricated from heavy gauge steel.
- All bolted construction - no welds
- Manual driven standard
- Motor drive available

