

## Hose Assembly Sleeving

### Styles USY and HMG

Style USY Polyurethane Sleeving	PART NUMBER	A I.D. (INCHES)	NOMINAL WALL THICKNESS (INCHES)	USUAL SERVICE AND TEMPERATURE RANGE
	USY-568	.568	.045	<p><b>Application:</b> Used over hose for protection of cover where high abrasion may exist.</p> <p><b>Temperature Range:</b> -40°F to +250°F Ultraviolet resistant</p> <p><b>Material:</b> Polyurethane</p> <p><b>Color:</b> Industrial yellow</p> <p><b>Lengths:</b> Available in 10 ft. lengths</p>
	USY-603	.603	.045	
	USY-668	.668	.045	
	USY-723	.723	.045	
	USY-768	.768	.045	
	USY-838	.838	.045	
	USY-856	.856	.045	
	USY-943	.943	.045	
	USY-1094	1.094	.045	
	USY-1168	1.168	.045	
	USY-1223	1.123	.045	
	USY-1328	1.328	.045	
	USY-1523	1.523	.045	
	USY-1672	1.672	.045	
	USY-2125	2.125	.060	

Style HMG Flame Retardant Polyurethane Sleeving MSHA Approved	PART NUMBER	A I.D. (INCHES)	NOMINAL WALL THICKNESS (INCHES)	USUAL SERVICE AND TEMPERATURE RANGE
	HMG-668	.668	.045	<p><b>Application:</b> Used over hose in mining applications for protection of cover where high abrasion may exist.</p> <p><b>Temperature range:</b> -40°F to + 250°F Ultraviolet resistant</p> <p><b>Material:</b> Flame retardant polyurethane</p> <p><b>Color:</b> Black</p> <p><b>Lengths:</b> Available in 10 ft. lengths</p>
	HMG-723	.723	.045	
	HMG-858	.858	.045	
	HMG-933	.933	.045	
	HMG-1133	1.133	.045	
	HMG-1243	1.243	.045	
	HMG-1303	1.303	.045	
	HMG-1523	1.523	.045	
	HMG-1604	1.604	.045	
	HMG-1975	1.975	.060	

**Hose  
Accessories**

