


**FULL PORT 600WOG
FORGED BRASS VALVE
ISO 9002 Manufacturer**

600 PSI non-shock cold water, gas,
oil - 150 PSI saturated steam

- Many options available.
- Minimal pressure drop due to large full size ports.
- Bottom loaded, pressure retaining stem.
- Pressure rated at 600 PSI (42 bars) WOG (non-shock) and 150 PSI (10.34 bars) saturated steam. Virgin TFE stem packing seal, thrust washer and seats.
- Vinyl insulator on heavy duty plated carbon steel handles.
- Fast 1/4 turn open or close operation.
- Low operating torque.
- Adjustable stem packing gland.
- Maximum operating temperature: 248°F (120°F)
- Minimum operating temperature: -20°F (-40°C)
- KV: Pressure drop m^3/h .
- Each valve individually tested.
- Forged Brass - for more strength.
- Tube ends to ANSI B1.20.1
- Hard chromium plated solid ball.
- Bottom entry, blow-out proof stem




Part #	Size
08BVSWT	1/2
12BVSWT	3/4
16BVSWT	1/2
20BVSWT	1-1/4
24BVSWT	1-1/2
32BVSWT	2-1/4

Mores sizes available upon request.

POS	Components	Materials
1	Body	Forged Brass
2	End Connection	Forged Brass
3	Ball	CP Brass
4	Ball Seats	P.T.F.E.
5	Stem	Brass
6	O-Ring	NBR 80
7	Handle	Steel
8	Nut	UNI 5771 Steel
9	Stem Seat	P.T.F.E.
10	Brass Ring	Brass
11	Stem Seat	P.T.F.E.
12	Nut	Brass

**FORGED BRASS VALVE
STANDARD PORT
ISO 9002 Manufacturer**

400 PSI non-shock cold water, gas,
oil - 125 PSI saturated steam



- Threaded ends to ANSI B1.20.1
- Each Valve individually tested.
- Hard chromium plated solid ball.
- Bottom entry, blow-out proof stem.
- Double stem packing, Teflon seats.

Mfg. in Italy,
Yellow Handle



**FORGED BRASS BALL VALVE IPS
SCREWED ENDS**

Part #	Size
100-403	1/2
100-404	3/4
100-405	1/2
100-406	1-1/4
100-407	1-1/2
100-408	2-1/4

POS	Components	Materials
1	Body	Forged Brass
2	End Connection	Forged Brass
3	Ball	CP Brass
4	Ball Stems	P.T.F.E
5	Stem. Antif. Seat	P.T.F.E
6	Stem Seat	P.T.F.E
7	Brass Ring	Brass
8	Stem	Brass
9	O-Rinig	NBR 80
10	Handle	Steel
11	Nut	Steel
12	Nut	Brass

