



**GAS BALL VALVES  
ISO 9002 Manufacturer**



- Bottom entry.
- Blow out proof design.
- Double viton O-Rings stem seals.
- Teflon seats for durability.
- Forged construction for greater strength.
- Larger ports for increased flow capacity.
- For use with natural, manufactured, mixed Liquefied petroleum and LP gas-air mixes.
- Manufactured to ANSI Z21.15, C.G.A. 9.1-M81, 9.2-M88, 1/2 psig. 372 also to A.G.A. 3-8, C.G.A. CR91-002, 2 psig.
- Reversible handle.
- May be used with water 400 WOG.

Materials	
<b>Handle Nut</b>	Steel
<b>Handle</b>	Epoxy Coated Aluminum
<b>Stem</b>	Brass ASTM B16
<b>Stem Seals</b>	Viton
<b>Seats</b>	Teflon PTFE
<b>Ball</b>	Chromium Plated Brass
<b>Body</b>	Forged Brass
<b>Connector</b>	Forged Brass

**GAS BALL VALVES**



Part #	Size
943-212 .....	1/2
943-213 .....	3/4

**APPLIANCE CONNECTOR VALVES  
FIP X FLARE**



Part #	Size
935-122 .....	3/8x1/2
935-123 .....	1/2x1/2
935-124 .....	5/8x3/4

**FLARE X FLARE GAS BALL VALVES  
AGA/UL GAS BALL VALVES**



Part #	Size
935-129 .....	3/8x3/8
935-130 .....	1/2x1/2

**Valves**